

proxSafe®

Key Management & Smart Storage Systems

The intelligent management system for keys and equipment with comprehensive audit and reporting capabilities. Control who can have access to individual items and restrict when they can be taken. Keys, radios, test equipment, tools, laptops and much more can now be managed efficiently with increased accountability so you know where they are and who has them. The powerful software Commander Connect allows easy configuration and control of access rights, time profiles and the creation of individual reports. That way you stay in control at all times and make the best use of your equipment.

Key cabinet with up to 64 slots

proxSafe maxx is a key management system that combines the advantages of a superior electronic system with an architecturally designed appearance. The smart design allows application in all situations where the visual appearance counts as well as reliable technology.

Thanks to the automatic roller shutter this cabinet needs only little space for operation. The cabinet opens and closes automatically.

A proxSafe maxx cabinet manages up to 64 keys.

Several cabinets can be combined to form a large complete system. Together with the proxSafe Terminal and the proxSafe Commander software this is an easy-to-install key management system which can be adapted to changing requirements at any time.

The generous resident memory of the user terminal allows operation even if the network fails, and a back-up battery bridges in case of power failures. An emergency key is provided in order to allow manual access to the cabinets and keyTags if necessary.

The keyTags and slots are designed for rugged operation. There are no electrical contacts on the keyTags. Dirt, corrosion or wear by daily operation are impossible. The proxSafe keyTags require no maintenance. All proxSafe housings are equipped with tamper contacts and 4 relays which can indicate various alarms via the network and locally.

Your benefits at a glance:

- **Power save mode for very long operation with backup battery**
- **Prevents unauthorized access with an automatically closing roller shutter**
- **Contactless technology, maintenance-free**
- **Convenient emergency opening**
- **4 outputs for local alarms**



maxx 32



maxx 64

Technical Data

Dimensions WxHxD /

Weight:

maxx 32	515 x 600 x 210 mm / 17 kg
maxx 64	515 x 600 x 210 mm / 28 kg

Housing Material: sheet steel, powder-coated, ASA, PC

Colour: similar to RAL 9006

Operating

Temperature: +5...+50 °C (+41...+122 °F)

Relative Humidity: 5...95 %, non-condensing

Power Requirement: 110...240 VAC

keyTag Frequency: 125 kHz

Digital Output: 4x 30 VDC / 1 A
for up to 16 Alarms